



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
A		REMOVED RB PLACARD FROM BOM & ADDED DYNO LABEL PER DAVE.	8/17/2009	RJC	-
1		-.004 OVER ALL LENGTH WAS .906, NOW .846, AND ADDED .721 TO .711 DIMENSION, PER DAVE AND ERA HELICOPTERS. ALSO ADDED -3G TO -.001 ENGRAVING.	8/26/2009	WP	DW
2	14-0198	CH'D TITLEBLOCK WAS RED BARN IS DART. -.001 CH'D DIMS WAS Ø.781 S.F. -.004 IS LIMITS Ø.7810-.7822, WAS .402 IS .398, DELETED DIMS 2X .507, 2X .293, (1.594). ADDED DIMS 4X .203 X 45°, 1.578. ADDED SECTION B-B. -.002 ADDED DETAIL C. -.004 CH'D DIMS WAS 3X Ø.201 THRU √ Ø.375 B.C. Ø1.172 @120° IS 3X Ø.150 THRU ALL √ Ø.325 X 82° ON Ø1.172 B.C. EQUALLY SPACED, WAS Ø.781 S.F. -.001 IS LIMITS Ø.7786-.7794. ADDED DETAIL D. -.005 ADDED B/O INFO #92210A146. CH'D TOLERANCE ON NON-CRITICAL DIMENSIONS.	10/27/2014	DPD	JAG
3	15-0362	UPDATED TO NEW DRAFTING STANDARDS. -.001 ADDED ENGRAVE S/N, "MADE IN USA" NOTE.	11/19/2015	DPD	JAG



NOTE:
REF. AGUSTA T/N: 3G6305G25831.



ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-001	1	BASE	6061		2
			-002	1	KNOB	4140 Q&T/4142 Q&T		3
			-003	1	THUMB NUT	4140 Q&T/4142 Q&T		4
			-004	1	BUSHING	BRASS		5
		B/O	-005	3	FLAT SOCKET HEAD CAP SCREW	S.S.	#6-32 UNC X 3/8 (MCMaster-CARR #92210A146)	1
		B/O	-006	4	HEX BOLT	STEEL	AN3-4A	1
		B/O	-007	1	PISTOL CASE WITH FOAM	PLASTIC	RSR GROUP #10137	NS






TITLE R/B RUBBER STOP ADJUSTMENT TOOL	
DWG NO. RBW6305G25831-3G	REV 3
MAT'L UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 .XX ± .01 .X ± .1	DRAWN BY: PERRITT APPROVED <i>D Weil</i> HEAT TREAT FINISH SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING	USED ON MODEL AW139
SCALE 1:2	DATE 7/9/2009
SHEET 1 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
2	14-0198	-001 CH'D DIMS WAS Ø.781 S.F. -004 IS LIMITS Ø.7810-.7822, WAS .402 IS .398. DELETED DIMS 2X .507, 2X .293, (1.594). ADDED DIMS 4X .203 X 45°, 1.578. ADDED SECTION B-B.	10/27/2014	DPD
3	15-0362	-001 ADDED ENGRAVE S/N, "MADE IN USA" NOTE.	11/19/2015	DPD



SECTION B-B



DETAIL A

(001)




BASE

NOTE:
1 MACHINE ENGRAVE T/N, "FWD", & ARROW
.21 LETTER HEIGHT.

DART AEROSPACE			
TITLE R/B RUBBER STOP ADJUSTMENT TOOL			
DWG NO. RBW6305G25831-3G-001			REV 3
MAT'L 6061		DRAWN BY: PERRITT	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		APPROVED <i>D. Weil</i>	
.XXX ± .005		HEAT TREAT	
.XX ± .01		FINISH RED ANODIZE	
.X ± .1		SPEC MIL-A-8625, TYPE II, CLASS II	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R		USED ON MODEL	
2. DIMENSIONAL LIMITS APPLY AFTER PLATING		AW139	
SCALE 2:3	DATE 7/9/2009	SHEET 2 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
2	14-0198	-002 ADDED DETAIL C.	10/27/2014	DPD	JAG



-002


KNOB

DART AEROSPACE	
TITLE R/B RUBBER STOP ADJUSTMENT TOOL	
DWG NO. RBW6305G25831-3G-002	REV 3
MAT'L 4140 Q&T/4142 Q&T	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH YELLOW ZINC
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AW139
SCALE 1:1	DATE 7/9/2009
SHEET 3 OF 5	



This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED

Ø 1.94
MED. KNURL



M12 x 1 THRU ALL






(-003)

THUMB NUT

DART AEROSPACE	
TITLE R/B RUBBER STOP ADJUSTMENT TOOL	
DWG NO. RBW6305G25831-3G-003	REV 3
MAT'L 4140 Q&T/4142 Q&T	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH YELLOW ZINC
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AW139
SCALE 1:1	DATE 7/9/2009
SHEET 4 OF 5	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		-004 OVER ALL LENGTH WAS .906, NOW .846, AND ADDED .721 TO .711 DIMENSION.	8/26/2009	WP	DW
2	14-0198	-004 CH'D DIMS WAS 3X Ø.201 THRU ∇ Ø.375 B.C. Ø1.172 @120° IS 3X Ø.150 THRU ALL ∇ Ø.325 X 82° ON Ø1.172 B.C. EQUALLY SPACED, WAS Ø.781 S.F. -001 IS LIMITS Ø.7786-.7794. ADDED DETAIL D.	10/27/2014	DPD	JAG



-004
 BUSHING

DART AEROSPACE	
TITLE R/B RUBBER STOP ADJUSTMENT TOOL	
DWG NO. RBW6305G25831-3G-004	REV 3
MAT'L BRASS	DRAWN BY: PERRITT
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVED <i>D Weil</i>
.XXX ± .005 FRACTIONS ± 1/8	HEAT TREAT
.XX ± .01 ANGLES ± 5°	FINISH
.X ± .1	SPEC
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	USED ON MODEL
2. DIMENSIONAL LIMITS APPLY AFTER PLATING	AW139
SCALE 1:1	DATE 7/9/2009
SHEET 5 OF 5	